



1108-H Series 重型

日式轮系列(重型)

Heavy Duty General Purposes Caster (Japanese Style)

- 转动灵活宁静, 脚架已有特殊加强, 强度大幅度提升及抗冲击, 另有侧刹可供选择
- Reinforce fork design to further improve load rating and impact resistance, Side lock brake is available.

载重 Load
140-300kg



» 特色区 Features



侧刹
Side Lock Brake



波盘防尘盖
Swivel Dust Cover



轮子可附金属防尘盖
Metal Thread Guard

» 轮子选项 Wheel Options



铁芯日式橡胶轮
Rubber on Steel Core



尼龙轮
Nylon



高科技耐磨聚氨酯(尼龙芯)
PU on PA Core



W全效轮
W Resolute



滚珠轴承
Ball Bearing



铝芯AQPU
QPU on AL Core



EQPU轮
EQPU



铝芯橡胶轮
Rubber on AL Core



WMRC轮
WMRC

**» 活动底板规格 SWIVEL TOP PLATE SIZE AND BOLT HOLE SPACING**

脚轮尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
4", 5", 6"活动底板 4", 5", 6" Swivel plate	101x101 mm (4"x 4")	78 x 78 mm (3-1/16"x 3-1/16")	10 mm (3/8")

» 固定底板规格 RIGID TOP PLATE SIZE AND BOLT HOLE SPACING

脚轮尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
5", 6"固定底板 5", 6" Rigid plate	91 x 140 mm (3-9/16"x5-1/2")	55 x 105 mm (2-1/8"x 4-1/8")	10 mm (3/8")

 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
100mmx32mm (4"x1-1/4")	250 kgs(550 lbs)	尼龙轮 Nylon	—	1108-H-04-07-2	1108-H-04-07-4	滚珠轴承 Ball Bearing	138mm (5-7/16")	活动87.5mm Swivel 87.5mm 侧刹87.5mm Swivel W/Side brake 87.5mm
100mmx36mm (4"x1-7/16")	270 kgs(594 lbs)	铝芯AQP(圆弧) QPU on AL Core (Round)	—	1108-H-04-87-2	1108-H-04-87-4			
	140 kgs(308 lbs)	W全效轮 W Resolute	—	1108-H-04-64-2	1108-H-04-64-4			
100mmx40mm (4"x1-9/16")	300 kgs(660 lbs)	铝芯AQP(圆弧) QPU on AL Core (Round)	—	1108-H-04-87(40)-2	1108-H-04-87(40)-4			
	200 kgs(440 lbs)	铝芯橡胶轮 Rubber on AL Core	—	1108-H-04-22-2	1108-H-04-22-4	滚珠轴承 Ball Bearing	168mm (6-5/8")	活动98.5mm Swivel 98.5mm 侧刹98.5mm Swivel W/Side brake 98.5mm
125mmx38mm (5"x1-1/2")	160 kgs(352 lbs)	W全效轮 W Resolute	1108-H-05-64-1	1108-H-05-64-2	1108-H-05-64-4			
125mmx40mm (5"x1-9/16")	300 kgs(660 lbs)	尼龙轮 Nylon	1108-H-05-07-1	1108-H-05-07-2	1108-H-05-07-4			
	300 kgs(660 lbs)	铝芯AQP(圆弧) QPU on AL Core (Round)	1108-H-05-87-1	1108-H-05-87-2	1108-H-05-87-4			
	300 kgs(660 lbs)	EQPU(圆弧) EQPU (Round)	1108-H-05-81-1	1108-H-05-81-2	1108-H-05-81-4			
	250 kgs(550 lbs)	铝芯橡胶轮 Rubber on AL Core	1108-H-05-22-1	1108-H-05-22-2	1108-H-05-22-4			
150mmx38mm (6"x1-1/2")	180 kgs(396 lbs)	W全效轮 W Resolute	1108-H-06-64-1	1108-H-06-64-2	1108-H-06-64-4	滚珠轴承 Ball Bearing	191mm (7-1/2")	活动113mm Swivel 113mm 侧刹113mm Swivel W/Side brake 113mm
150mmx40mm (6"x1-9/16")	160 kgs(352 lbs)	铁芯日式橡胶轮 Rubber on Steel Core	1108-H-06-18-1	1108-H-06-18-2	1108-H-06-18-4			
	300 kgs(660 lbs)	WMRC轮 WMRC	1108-H-06-45-1	1108-H-06-45-2	1108-H-06-45-4			
	280 kgs(616 lbs)	铝芯橡胶轮 Rubber on AL Core	1108-H-06-22-1	1108-H-06-22-2	1108-H-06-22-4			
150mmx42mm (6"x1-5/8")	300 kgs(660 lbs)	铝芯AQP(圆弧) QPU on AL Core (Round)	1108-H-06-87-1	1108-H-06-87-2	1108-H-06-87-4			
	300 kgs(660 lbs)	EQPU(圆弧) EQPU (Round)	1108-H-06-81-1	1108-H-06-81-2	1108-H-06-81-4			
150mmx44mm (6"x1-3/4")	200 kgs(440 lbs)	高科技耐磨聚氨酯(尼龙芯) PU on PA Core	1108-H-06-34-1	1108-H-06-34-2	1108-H-06-34-4			