



1115 Series

弹簧轮系列(常规)


Spring-loaded Caster (Regular)

- 属得胜专利产品，避震，超重负载，多款供选择，采用超厚板材及高级弹簧，品质、工艺明显优于市场上同类产品。

- DERSHENG'S patented products, shock-absorbing, extreme heavy-duty, diversified selection. Made of super thick steel and high quality spring, outperforming most products from competitors.



特色区 Features



AK煞(For 4",5",6",8")
Swivel W/Center Lock(AK type)




BCD煞(中煞)(For 10" only)
Swivel W/Center Lock Brake




PU轮面可以变化硬度
Different PU
tread hardness available



滚珠轴承
Ball Bearing



轮子可附金属防尘盖(供选择)
Metal Thread Guard(optional)



轮子可附塑料防尘盖(供选择)
Plastic Thread Guard(optional)

轮子选项 Wheel Options



铁芯聚氨酯
PU on Cast



QPU轮
QPU



铝芯AQP
QPU on AL Core



环保牵引NBR
Non-marking NBR Rubber
on Cast



铁芯NBR橡胶轮(叉车料)
NBR Rubber on Cast



EPU轮
EPU



EQPU轮
EQPU



VPU轮
VPU



VQPU轮
VQPU



尼龙轮
Nylon



WMRC轮
WMRC



» 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
4" 5" 6" 8"	110 x 140mm (4-11/32" x 5-1/2")	75 x 110mm(常規標準底板) (2-15/16" x 4-11/32")	12 mm (1/2")
	110 x 140mm (4-11/32" x 5-1/2")	80 x 105mm(歐規孔距) (3-5/32" x 4-1/8"(European Plate))	12 mm (1/2")
	130 x 165mm (5-1/8" x 6-1/2")	100 x 130mm (3-15/16" x 5-1/8")	12 mm (1/2")
	114 x 159mm (4-1/2" x 6-1/4")	73.8 x 129.4mm (2-29/32" x 5-3/32")	12 mm (1/2")
10"	130 x 167mm (5-1/8" x 6-9/16")	85 x 140mm (3-11/32" x 5-1/2")	12 mm (1/2")

 輪徑x輪寬 DiameterxWidth	 載重 Load	 材質 Material	型號 Item No.			 軸承 Bearing	 總高 Overall Height	 回旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
100mm x 32mm (4" x 1-1/4")	150 kgs (330 lbs)	尼龍輪 Nylon	1115-04-07-1	1115-04-07-2	1115-04-07-4	滾珠 Ball Bearing	198mm (7-13/16")	活動 96mm AK煞 164mm Swivel 96mm Swivel W/AK lock brake 164mm
100mm x 36mm (4" x 1-7/16")	200 kgs (440 lbs)	鐵芯聚氨酯 PU on Cast	1115-04-33-1	1115-04-33-2	1115-04-33-4			
	200 kgs (440 lbs)	鋁芯AQPU QPU on AL Core	1115-04-87-1	1115-04-87-2	1115-04-87-4			
	250 kgs (550 lbs)	QPU輪 QPU	1115-04-80-1	1115-04-80-2	1115-04-80-4			
100mm x 38mm (4" x 1-1/2")	150 kgs (330 lbs)	保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-04-90-1	1115-04-90-2	1115-04-90-4	滾珠 Ball Bearing	210mm (8-9/32")	活動 132mm AK煞 194mm Swivel 132mm Swivel W/AK lock brake 194mm
	150 kgs (330 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-04-04-1	1115-04-04-2	1115-04-04-4			
125mm x 40mm (5" x 1-9/16")	200 kgs (440 lbs)	尼龍輪 Nylon	1115-05-07-1	1115-05-07-2	1115-05-07-4			
	200 kgs (440 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-05-90-1	1115-05-90-2	1115-05-90-4			
	250 kgs (550 lbs)	鋁芯AQPU QPU on AL Core	1115-05-87-1	1115-05-87-2	1115-05-87-4			
	200 kgs (440 lbs)	鐵芯聚氨酯 PU on Cast	1115-05-33-1	1115-05-33-2	1115-05-33-4			
	200 kgs (440 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-05-04-1	1115-05-04-2	1115-05-04-4			
	250 kgs (550 lbs)	QPU輪 QPU	1115-05-80-1	1115-05-80-2	1115-05-80-4			
	250 kgs (550 lbs)	EPU輪 EPU	1115-05-78-1	1115-05-78-2	1115-05-78-4			
	350 kgs (770 lbs)	EQPU輪 EQPU	1115-05-81-1	1115-05-81-2	1115-05-81-4			
150mm x 40mm (6" x 1-9/16")	250 kgs (550 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-06-04-1	1115-06-04-2	1115-06-04-4	滾珠 Ball Bearing	225mm (8-27/32")	活動 146mm AK煞 200mm Swivel 146mm Swivel W/AK lock brake 200mm
	250 kgs (550 lbs)	尼龍輪 Nylon	1115-06-07-1	1115-06-07-2	1115-06-07-4			
	250 kgs (550 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-06-90-1	1115-06-90-2	1115-06-90-4			
	250 kgs (550 lbs)	WMRC輪 WMRC	1115-06-45-1	1115-06-45-2	1115-06-45-4			
150mm x 42mm (6" x 1-5/8")	250 kgs (550 lbs)	鐵芯聚氨酯 PU on Cast	1115-06-33-1	1115-06-33-2	1115-06-33-4			
	300 kgs (660 lbs)	鋁芯AQPU QPU on AL Core	1115-06-87-1	1115-06-87-2	1115-06-87-4			
	300 kgs (660 lbs)	QPU輪 QPU	1115-06-80-1	1115-06-80-2	1115-06-80-4			
	300 kgs (660 lbs)	EPU輪 EPU	1115-06-78-1	1115-06-78-2	1115-06-78-4			
	400 kgs (880 lbs)	EQPU輪 EQPU	1115-06-81-1	1115-06-81-2	1115-06-81-4			
	400 kgs (880 lbs)	VPU輪 VPU	1115-06-82-1	1115-06-82-2	1115-06-82-4			
	500 kgs (1100 lbs)	VQPU輪 VQPU	1115-06-83-1	1115-06-83-2	1115-06-83-4			
150mm x 46mm (6" x 1-13/16")	300 kgs (660 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-06-04-1	1115-06-04-2	1115-06-04-4			



 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
200mm x 44mm (8" x 1-3/4")	300 kgs (660 lbs)	铁芯NBR橡胶轮 NBR Rubber on Cast	1115-08-04-1	1115-08-04-2	1115-08-04-4	滚珠 Ball Bearing	280mm (11-1/32")	活动 182mm AK煞 254mm Swivel 182mm Swivel W/AK lock brake 254mm
	300 kgs (660 lbs)	环保牵引NBR轮 Non-marking NBR Rubber on Cast	1115-08-90-1	1115-08-90-2	1115-08-90-4			
200mm x 50mm (8" x 2")	300 kgs (660 lbs)	铁芯聚氨酯 PU on Cast	1115-08-33-1	1115-08-33-2	1115-08-33-4			
	350 kgs (770 lbs)	QPU轮 QPU	1115-08-80-1	1115-08-80-2	1115-08-80-4			
	350 kgs (770 lbs)	EPU轮 EPU	1115-08-78-1	1115-08-78-2	1115-08-78-4			
	450 kgs (990 lbs)	EQPU轮 EQPU	1115-08-81-1	1115-08-81-2	1115-08-81-4			
	450 kgs (990 lbs)	VPU轮 VPU	1115-08-82-1	1115-08-82-2	1115-08-82-4			
	550 kgs (1210 lbs)	VQPU轮 VQPU	1115-08-83-1	1115-08-83-2	1115-08-83-4			
	300 kgs (660 lbs)	尼龙轮 Nylon	1115-08-07-1	1115-08-07-2	1115-08-07-4			
	300 kgs (660 lbs)	WMRC轮 WMRC	1115-08-45-1	1115-08-45-2	1115-08-45-4			
	350 kgs (770 lbs)	铝芯AQPU QPU on AL Core	1115-08-87-1	1115-08-87-2	1115-08-87-4			
250mm x 62mm (10" x 2-7/16")	500 kgs (1100 lbs)	QPU轮 QPU	1115-10-80-1	1115-10-80-2	1115-10-80-4	滚珠 Ball Bearing	353mm (13-29/32")	活动 213mm BCD煞 255mm Swivel 213mm Swivel W/Center lock 255mm
	500 kgs (1100 lbs)	VPU轮 VPU	1115-10-82-1	1115-10-82-2	1115-10-82-4	滚珠 Ball Bearing	355mm (14")	
	600 kgs (1320 lbs)	VQPU轮 VQPU	1115-10-83-1	1115-10-83-2	1115-10-83-4	滚珠 Ball Bearing	355mm (14")	
250mm x 63mm (10" x 2-1/2")	350 kgs (770 lbs)	铁芯NBR橡胶轮 NBR Rubber on Cast	1115-10-04-1	1115-10-04-2	1115-10-04-4	滚珠 Ball Bearing	355mm (14")	
	350 kgs (770 lbs)	环保牵引NBR轮 Non-marking NBR Rubber on Cast	1115-10-90-1	1115-10-90-2	1115-10-90-4	滚珠 Ball Bearing	353mm (13-29/32")	
254mm x 50mm (10" x 2")	300 kgs (660 lbs)	尼龙轮 Nylon	1115-10-07-1	1115-10-07-2	1115-10-07-4	滚珠 Ball Bearing	353mm (13-29/32")	
254mm x 62mm (10" x 2-7/16")	450 kgs (990 lbs)	铁芯聚氨酯 PU on Cast	1115-10-33-1	1115-10-33-2	1115-10-33-4	滚珠 Ball Bearing	353mm (13-29/32")	