



1119

Series 重型

鷹架輪系列

Scaffolding Caster

- 制动简易, 适用于脚手架。

- Design for Scaffolds.

载重 Load
350-420 kg



» 特色区 Features » 轮子选项 Wheel Options



中刹
Center Lock Brake



铁芯NBR橡胶轮
NBR Rubber on Cast



高科技耐磨聚氨酯
PU on PP Core



滚针轴承
Roller Bearing

滚珠轴承
Ball Bearing

» 插杆规格 STEM SIZE AND BOLT HOLE SPACING

编号 Suffix	插杆直径 Stem Size	插杆高度 x 孔位高度 Stem Height x Hole Height	孔尺寸 Bore Size
1	35 mm (1-3/8")	100 mm x 60 mm (3-15/16x 2-3/8")	11 mm (7/16")

轮径x轮宽 DiameterxWidth	载重 Load	材质 Material	型号 Item No.			轴承 Bearing	回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake		
150mmx50mm (6"x2")	350 kgs (770 lbs)	铁芯NBR橡胶轮 NBR Rubber on Cast	--	--	1119-06-04-4	滚针 Roller Bearing	煞车120mm Swivel W/Center lock 120mm
	350 kgs (770 lbs)	高科技耐磨聚氨酯 PU on PP Core	--	--	1119-06-31-4		
200mmx45mm (8"x1-3/4")	420 kgs (925 lbs)	铁芯NBR橡胶轮 NBR Rubber on Cast	--	--	1119-08-04-4	滚珠 Ball Bearing	煞车 143.5mm Swivel W/Center lock 143.5mm
200mmx50mm (8"x2")	420 kgs (925 lbs)	铁芯NBR橡胶轮 NBR Rubber on Cast	--	--	1119-08-04-4	滚针 Roller Bearing	煞车152mm Swivel W/Center lock 152mm
	420 kgs (925 lbs)	高科技耐磨聚氨酯 PU on PP Core	--	--	1119-08-31-4		