



1135 Series

全塑系列

Med-Glide Series Caster (All Plastic)

- 无污染 ● 超静音 ● 防生锈 ● 弹性佳
- 低阻力 ● 转动灵活 ● 耐冲材质 ● 专利产品
- 产品轻量化且坚固耐用
- 可另选购有抗菌效果之全效轮或TPR轮
- 适用于医疗器材设备、家具置物架、食品工厂、学校、办公室等场所。
- 另有不锈钢材质的五金件可供选择
- 可提供无磁脚轮

- High grade synthetic housing
Smooth and easy rolling, these casters noticeably reduce the effort to operate equipment
Highly effective Thread guards prevent failure from strings and other debris.
Specifically designed for healthcare and institutional applications where silence is essential.
Corrosion resistant with non-marking wheels
- Ball bearing swivel head
- Directional lock also available
- Stainless steel components are also available
- Magnetic Free Caster also available



» 特色区 Features



双刹
Total Lock Brake



定向刹
Directional
Lock Brake



无磁脚轮
Magnetic Free
Caster

» 轮子选项 Wheel Options



全效轮
Resolute



超级人造胶
TPR on PP Core



铝芯AQPU
QPU on AL Core



滚珠轴承
Ball Bearing

» 底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

规格 Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
4" 5"	69X96mm	45X75mm(高级底板) *	M8
4" 5"	69X96mm	49X74.5mm(斜孔底板) *	M8

* 有固定架可供选择 (Fixed Caster is available. Please consult the factory.)



» 插杆规格 CYLINDRICAL STEM SPECIFICATION

规格 Size	插杆直径 X 长度 Diameter x Length	孔位高度 Hole Height	孔尺寸 Bore Size
4" 5"	21.6X56mm	—	C型环 (Grip Ring)
4" 5"	21.5X44.5mm	25.4mm *	#10 X 24UNC+C型环(Grip Ring)
4" 5"	28X30mm	19mm *	M8
4" 5"	28X40mm	19mm *	M8

* 有固定架可供选择 (Fixed Caster is available. Please consult the factory.)

» 丝扣规格 THREADED STEM SPECIFICATION

规格 Size	丝扣牙径 X 长度 Threaded Size	规格 Size	丝扣牙径 X 长度 Threaded Size
4" 5"	3/8-16UNCX32mm	4" 5"	M12X25mm
4" 5"	M12X25mm (不锈钢SS)	4" 5"	1/2-12UNCX25mm
4" 5"	1/2-20UNCX25mm (不锈钢SS)	4" 5"	M16X30mm

» 空铆规格 SINGLE BOLT HOLE

规格 Size	孔径 Centre Hole	规格 Size	孔径 Centre Hole
4" 5"	10.5mm	4" 5"	12.5mm

 轮径x轮宽 DiameterxWidth	规 格 Specification	 载重 Load	 材质 Material	 品号 Item No.				 轴承 Bearing	 总高 Overall Height	 偏心距 Offset	 回旋半径 Swivel radius
				固定 Fixed	活动 Swivel	双刹 Total Lock Brake	定向刹 Directional Lock				
100mmx31mm (4"x1-1/4")	四角底板 Plate	90kgs (198lbs)	全效轮 Resolute	11350400451013	11350400452013	11350400454013	11350400454213	滚珠轴承 Ball Bearing	146mm (5"-3/4")	34mm (1"-11/32")	活动 84mm 活刹 105.5mm Swivel 84mm Swivel W/Total Lock Brake 105.5mm
		90kgs (198lbs)	超级人造胶 TPR on PP Core	11350400261013	11350400262013	11350400264013	11350400264213				
	丝扣 Threaded Stem	90kgs (198lbs)	全效轮 Resolute	—	11350400455013	11350400456013	—		145mm (5"-45/65")		
		90kgs (198lbs)	超级人造胶 TPR on PP Core	—	11350400265013	11350400266013	—				
	空铆 Single Bolt Hole	90kgs (198lbs)	全效轮 Resolute	—	11350400459213	11350400459413	—		144mm (5"-43/64")		
		90kgs (198lbs)	超级人造胶 TPR on PP Core	—	11350400269213	11350400269413	—				
	插杆 Cylindrical Stem	90kgs (198lbs)	全效轮 Resolute	11350400457313	11350400457013	11350400458013	11350400458213		144mm (5"-43/64")		
		90kgs (198lbs)	超级人造胶 TPR on PP Core	11350400267313	11350400267013	11350400268013	11350400268213				
125mmx31mm (5"x1-1/4")	四角底板 Plate	100kgs (220lbs)	全效轮 Resolute	11350500451013	11350500452013	11350500454013	11350500454213	滚珠轴承 Ball Bearing	175mm (6"-57/64")	44.5mm (1"-3/4")	活动 107mm 活刹 124.5mm Swivel 107mm Swivel W/Total Lock Brake 124.5mm
		100kgs (220lbs)	超级人造胶 TPR on PP Core	11350500261013	11350500262013	11350500264013	11350500264213				
		100kgs (220lbs)	铝芯AQPU QPU on AL Core	1135-05-87-1	1135-05-87-2	1135-05-87-4	1135-05-87-9				
	丝扣 Threaded Stem	100kgs (220lbs)	全效轮 Resolute	—	11350500455013	11350500456013	—		174mm (6"-27/32")		
		100kgs (220lbs)	超级人造胶 TPR on PP Core	—	11350500265013	11350500266013	—				
		100kgs (220lbs)	铝芯AQPU QPU on AL Core	—	1135-05-87-2	1135-05-87-4	—				
	空铆 Single Bolt Hole	100kgs (220lbs)	全效轮 Resolute	—	11350500459213	11350500459413	—		173mm (6"-13/16")		
		100kgs (220lbs)	超级人造胶 TPR on PP Core	—	11350500269213	11350500269413	—				
		100kgs (220lbs)	铝芯AQPU QPU on AL Core	—	1135-05-87-2	1135-05-87-4	—				
	插杆 Cylindrical Stem	100kgs (220lbs)	全效轮 Resolute	11350500457313	11350500457013	11350500458013	11350500458213		173mm (6"-13/16")		
		100kgs (220lbs)	超级人造胶 TPR on PP Core	11350500267313	11350500267013	11350500268013	11350500268213				
		100kgs (220lbs)	铝芯AQPU QPU on AL Core	1135-05-87-1	1135-05-87-2	1135-05-87-4	1135-05-87-9				