


**1169 Series****水平调节轮系列****Height Adjustment Caster**

- 水平调节轮系列脚轮适用于电气自动化设备类、半导体设备类、医疗机械类、其他机台、机柜设备类，适用于3T以下的设备支撑要求，具有重型支撑、水平调节、可移动、环保清洁等专业特点，可根据客户需求提供客製化服务，详情请洽工厂。
- The height adjustment casters are suitable for electrical automation equipment, semiconductor equipment, medical machinery, other machine tools, and cabinet equipment. They are suitable for equipment support requirements below 3 tons, with professional features such as heavy-duty support, horizontal adjustment, mobility, and environmentally friendly cleaning. Customization services are available according to customer needs. For details, please contact the factory.

载重 Load
50-1500 kg

**» 轮子选项 Wheel Options**

PA轮
PA wheel

» 底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

规格 Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
GD - 40F	55 x 55 mm (2-1/8" x 2-1/8")	42 x 42 mm (1-5/8" x 1-5/8")	M6
GD - 60F	73 x 73 mm (2-7/8" x 2-7/8")	58 x 58 mm (2-1/4" x 2-1/4")	M6
GD - 80F	90 x 90 mm (3-1/2" x 3-1/2")	70 x 70 mm (2-3/4" x 2-3/4")	M8
GD - 100F、GD - 120F	95 x 95 mm (3-3/4" x 3-3/4")	70 x 70 mm (2-3/4" x 2-3/4")	M10
GD - 150F	100 x 100 mm (4" x 4")	70 x 70 mm (2-3/4" x 2-3/4")	M12

» 丝扣规格 THREADED STEM SPECIFICATION

规格 Size	丝扣牙径 x 长度 - 牙矩 Threaded Size	规格 Size	丝扣牙径 x 长度 - 牙矩 Threaded Size
GD - 40S	M8x30-P1.25	GD - 60S、GD - 80S	M12x40-P2
GD - 100S、GD - 120S	M16x50-P2		



规格 Size	 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	型号 Item No.			 轴承 Bearing	 总高+可调高度 Overall Height	 回旋半径 Swivel radius
				固定 Fixed	活动 Swivel	刹车 Brake			
GD - 40	40mm x 20mm (1-5/8" x 3/4")	50kgs (110 lbs)	PA轮 PA wheel	—	1169-0150-07-2	—	无 N/A	71+10mm (2-3/4")	51mm
GD - 60	50mm x 25mm (2" x 1")	250kgs (551 lbs)	PA轮 PA wheel	—	1169-0200-07-2	—		82+10mm (3-1/4")	63mm
GD - 80	61mm x 28mm (2-3/8" x 1-1/8")	500kgs (1102 lbs)	PA轮 PA wheel	—	1169-0250-07-2	—		103+15mm (4")	78mm
GD - 100	72mm x 30mm (2-7/8" x 1-1/8")	750kgs (1653 lbs)	PA轮 PA wheel	—	1169-0250-07-2	—		120+12mm (4-3/4")	90.5mm
GD - 120	72mm x 30mm (2-7/8" x 1-1/8")	1000kgs (2204 lbs)	PA轮 PA wheel	—	1169-0250-07-2	—		120+12mm (4-3/4")	90mm
GD - 150	95mm x 55mm (3-3/4" x 2-1/8")	1500kgs (3306 lbs)	PA轮 PA wheel	—	1169-0350-07-2	—		132+15mm (5-1/4")	116mm

使用标准

*4pcs脚轮支撑承重标准为单个脚轮承重x2

**脚轮行走状态应在平整地面、行走速度≤1km/h, 短距离行走。

Using standard:

*The load-bearing standard for 4pcs caster support is twice the load-bearing capacity of a single caster.

** Dynamic loading should be on a flat surface, walking speed ≤ 1km/h, short-distance walking.