

HDR&WHDR輪

	輪面硬度		95°±5° Shore A
	溫度範圍		-20°C to +60°C
	滾動順暢		非常優秀
	音量		良好
	保護地板		良好



[HDR]

[WHDR]

輪面

為熱塑性橡膠彈性體(TPR)，便於保護地面，無痕，操作舒適，承受大載重，滾動阻力和旋轉阻力小，耐許多侵蝕性物質的腐蝕。顏色：灰色。
 硬度為 95°±5° Shore A。
 與輪體的化學黏合不可分解。

輪體

採用優質耐衝擊聚丙烯。

特色

- 大載重，保護地面，正常使用免維護。
- 適用溫度範圍：-20° C至 +60° C。



中輕型 HDR



品号	轮径 (D)[mm]	轮宽 (T2)[mm]	载重 [kg(lbs)]	轴承内径 Ø(d)[mm]	中宽 (T1)[mm]	轮面	轴承
1235030017	3" (75mm)	1" (27mm)	90kg / 200lbs	Ø 6mm	33mm	圆弧	滚珠轴承
1235030018	3" (75mm)	1-1/4" (31mm)	120kg / 265lbs	Ø 10mm	41mm		
1235040005	4" (100mm)	1-1/4" (31mm)	160kg / 350lbs	Ø 10mm	41mm		
1235050004	5" (125mm)	1-1/4" (31mm)	180kg / 400lbs	Ø 10mm	41mm		
1235060016	6" (150mm)	1-1/4" (31mm)	180kg / 400lbs	Ø 10mm	41mm		

中輕型 WHDR



品号	轮径 (D)[mm]	轮宽 (T2)[mm]	载重 [kg(lbs)]	轴承内径 Ø(d)[mm]	中宽 (T1)[mm]	轮面	轴承
1235030019	3" (75mm)	1-1/4" (31mm)	140kg / 310lbs	Ø 10mm	41mm	平面	滚珠轴承
1235040014	4" (100mm)	1-1/4" (31mm)	180kg / 400lbs	Ø 10mm	41mm		
1235050016	5" (125mm)	1-1/4" (31mm)	200kg / 440lbs	Ø 10mm	41mm		
1235060017	6" (150mm)	1-1/4" (31mm)	200kg / 440lbs	Ø 10mm	41mm		

重型 HDR



品号	轮径 (D)[mm]	轮宽 (T2)[mm]	载重 [kg(lbs)]	轴承内径 Ø(d)[mm]	中宽 (T1)[mm]	轮面	轴承
1235040019	4" (100mm)	2" (50mm)	228kg / 500lbs	Ø 13mm	62mm	圆弧	精密长珠轴承
1235050037	5" (125mm)	2" (50mm)	261kg / 575lbs	Ø 13mm	62mm		
1235060018	6" (150mm)	2" (50mm)	295kg / 650lbs	Ø 13mm	62mm		
1235080008	8" (200mm)	2" (50mm)	318kg / 700lbs	Ø 13mm	62mm		
1235040029	4" (100mm)	2" (50mm)	270kg / 600lbs	Ø 13mm	62mm	平面	
1235050038	5" (125mm)	2" (50mm)	340kg / 750lbs	Ø 13mm	62mm		
1235060019	6" (150mm)	2" (50mm)	408kg / 900lbs	Ø 13mm	62mm		
1235080009	8" (200mm)	2" (50mm)	430kg / 950lbs	Ø 13mm	62mm		

重型 WHDR



品号	轮径 (D)[mm]	轮宽 (T2)[mm]	载重 [kg(lbs)]	轴承内径 Ø(d)[mm]	中宽 (T1)[mm]	轮面	轴承
1235040030	4" (100mm)	2" (50mm)	270kg / 600lbs	Ø 13mm	62mm	平面	精密长珠轴承
1235050039	5" (125mm)	2" (50mm)	340kg / 750lbs	Ø 13mm	62mm		
1235060020	6" (150mm)	2" (50mm)	408kg / 900lbs	Ø 13mm	62mm		
1235080010	8" (200mm)	2" (50mm)	430kg / 950lbs	Ø 13mm	62mm		