

NBR系列

重型轮

弹力橡胶外包+铁芯/铸铁芯

	轮面硬度		85° ± 5° shore A
	温度范围		-25°C to +80°C
	滚动顺畅		优秀
	音量		非常优秀
	保护地板		非常优秀



轮面

由高品质的弹力橡胶制成，得胜铁芯橡胶轮轮面硬度是85°±5°，具有极佳的操作舒适性，优秀的地板保护作用及避震功能。颜色：黑色。

轮框

内框：铁芯/铸铁芯

特色

- 抗化学、溶剂及侵蚀
- 适用环境温度：-25°C ~ +80°C
- 在正常使用情况下，无需维修



品号	轮径 (D) [mm]	轮宽 (T2) [mm]	载重 [kg(lbs)]	轴承内径 Ø(d) [mm]	中宽 (T1) [mm]	轮面	轴承
12040404151371	100	37	120kgs (264lbs)	15	34	平面	精密滚珠 轴承
12040404151271	100	37	120kgs (264lbs)	17	34		
12040405151271	125	40	150kgs (330lbs)	17	42		
12040406156371	150	40	150kgs (330lbs)	17	42		
12040406186171	150	46	250kgs (551lbs)	17	46		
12040306306171	150	57	250kgs (551lbs)	17	57		
12040408181471	200	44	300kgs (661lbs)	17	50		
12040408181771	200	44	300kgs (661lbs)	20	50		
12040408181571	200	44	300kgs (661lbs)	25	50		
12040408181671	200	46	300kgs (661lbs)	17	46		
12040408286171	200	70	400kgs (881lbs)	17	68		
12040408286271	200	70	400kgs (881lbs)	20	68		
12040408286371	200	70	400kgs (881lbs)	25	68		
12040410206171	250	50	400kgs (881lbs)	17	50	圆弧	
12040410206371	250	50	400kgs (881lbs)	20	50		
12040410206671	250	50	400kgs (881lbs)	25	50		
12040410256171	250	63	450kgs (992lbs)	17	63		
12040410256271	250	63	450kgs (992lbs)	20	63		
12040410256371	250	63	450kgs (992lbs)	25	63		
12040410286171	254	71	450kgs (992lbs)	17	69		
12040410286271	254	71	450kgs (992lbs)	20	69		
12040410286371	254	71	450kgs (992lbs)	25	69		
12040412606171	302	150	650kgs (1433lbs)	30	150		
12040412606271	302	150	650kgs (1433lbs)	35	150		
12040412406171	304	105	600kgs (1323lbs)	25	106		
12040412406371	304	105	600kgs (1323lbs)	30	106		
12040412406471	304	105	600kgs (1323lbs)	35	106		
12040412206471	306	49	500kgs (1102lbs)	20	51		
12040412206171	306	49	500kgs (1102lbs)	25	51		
12040412301471	300	76	550kgs (1213lbs)	25	74		
12040412306171	300	76	550kgs (1213lbs)	30	74		
12040412306271	300	76	550kgs (1213lbs)	35	74		

