


PP



	轮面硬度		65°±5° Shore A
	温度范围		-10°C to +60°C
	滚动顺畅		非常优秀
	音量		良好
	保护地板		良好

轮面

PP 化学名聚丙烯，耐热性好，刚硬有韧性，抗疲劳，抗应力开裂，不受湿度环境影响，耐腐蚀，耐油，耐酸，耐碱等有机溶剂，无气味并可回收；轮子载重大，滚动阻力小。

PP适用温度范围：-10°C~+60°C。

硬度为65°±5°share D

特色

- 运转低阻力
- 适用温度范围：-10°C~+60°C
- 正常使用免维护



品号	轮径 (D) [mm]	轮宽 (T2) [mm]	载重 [kg(lbs)]	轴承内径 Ø(d) [mm]	中宽 (T1) [mm]	轮面
12022951080200	38	16.5	20kgs(44lbs)	6	20.5	圆弧
12022902006200	50	21	25kgs(55lbs)	6.2	24	
12022952081200	65	25	30kgs(66lbs)	6	30.5	
12022952004100	65	25	30kgs(66lbs)	8	30.5	
12022952130100	62.5	35	30kgs(66lbs)	10.2	39	
12022903131500	76	32	35kgs(77lbs)	10.2	39.5	
12022903137100	75	25	35kgs(77lbs)	8	30	
12022904151400	100	35	90kgs(198lbs)	13	35	
12022904154100	100	35	90kgs(198lbs)	13	35	
12022904100100	100	25	90kgs(198lbs)	8	30.5	
12022905201300	125	48	100kgs(220lbs)	10.2	54.5	
12022905130100	125	35	100kgs(220lbs)	13	39	平面