



# 1125 Series Heavy Duty Institutional Caster

- Pressed steel yoke with good outlook and added strength; ideal for application requiring both aesthetic and heavy load.

Load  
140-400 kg



## » Features



Center Lock Brake  
(For 8" only)



Side Lock Brake  
(For 4", 5", 6" only)



Thread guard

## » Wheel Options

QPU On AL Core



W Resolute

QPU



CPD

PU on Cast



Rubber on Cast

NBR Rubber on Cast




Resilient Rubber on PA core

Nylon



WMRC



Ball Bearing


## » TOP PLATE SIZE AND BOLT HOLE SPACING

Suffix	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
1	105 x 115mm (4-1/8" x 4-1/2")	70 x 85 mm (2-5/8"~3"x3"~3-5/8")	9.5mm (3/8")



 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
100mm x 32mm (4" x 1-1/4")	200 kgs (440 lbs)	Nylon	1125-04-07-1	1125-04-07-2	1125-04-07-4	Ball Bearing	136.5mm (5-3/8")	Swivel 87mm Swivel W/Brake 99.5mm
	150 kgs (330 lbs)	CPD	1125-04-49-1	1125-04-49-2	1125-04-49-4			
100mm x 34mm (4" x 1-1/3")	200 kgs (440 lbs)	PU on Cast	1125-04-33-1	1125-04-33-2	1125-04-33-4	Ball Bearing	136.5mm (5-3/8")	Swivel 87mm Swivel W/Brake 99.5mm
	300 kgs (660 lbs)	QPU	1125-04-80-1	1125-04-80-2	1125-04-80-4			
	150 kgs (330 lbs)	Resilent Rubber on PA core	1125-04-10-1	1125-04-10-2	1125-04-10-4			
100mm x 36mm (4" x 1-7/16")	325 kgs (715 lbs)	QPU on AL Core (Round)	1125-04-87-1	1125-04-87-2	1125-04-87-4	Ball Bearing	136.5mm (5-3/8")	Swivel 87mm Swivel W/Brake 99.5mm
100mm x 38mm (4" x 1-1/2")	150 kgs (330 lbs)	Rubber on Cast	1125-04-03-1	1125-04-03-2	1125-04-03-4	Ball Bearing	136.5mm (5-3/8")	Swivel 87mm Swivel W/Brake 99.5mm
	140 kgs (308 lbs)	W Resolute	1125-04-64-1	1125-04-64-2	1125-04-64-4			
	150 kgs (330 lbs)	NBR Rubber on Cast	1125-04-04-1	1125-04-04-2	1125-04-04-4			
100mm x 40mm (4" x 1-9/16")	350 kgs (770 lbs)	QPU on AL Core (Round)	1125-04(40)-87-1	1125-04(40)-87-2	1125-04(40)-87-4	Ball Bearing	136.5mm (5-3/8")	Swivel 87mm Swivel W/Brake 99.5mm
125mm x 38mm (5" x 1-1/2")	170 kgs (375 lbs)	Resilent Rubber on PA core	1125-05-10-1	1125-05-10-2	1125-05-10-4	Ball Bearing	136.5mm (6-7/16")	Swivel 101.5mm Swivel W/Brake 101.5mm
	250 kgs (550 lbs)	W Resolute	1125-05-64-1	1125-05-64-2	1125-05-64-4			
125mm x 40mm (5" x 1-9/16")	250 kgs (550 lbs)	Nylon	1125-05-07-1	1125-05-07-2	1125-05-07-4	Ball Bearing	163mm (6-7/16")	Swivel 101.5mm Swivel W/Brake 101.5mm
	200 kgs (440 lbs)	CPD	1125-05-49-1	1125-05-49-2	1125-05-49-4			
	250 kgs (550 lbs)	PU on Cast	1125-05-33-1	1125-05-33-2	1125-05-33-4			
	350 kgs (770 lbs)	QPU	1125-05-80-1	1125-05-80-2	1125-05-80-4			
	200 kgs (440 lbs)	NBR Rubber on Cast	1125-05-04-1	1125-05-04-2	1125-05-04-4			
	350 kgs (770 lbs)	QPU on AL Core (Round)	1125-05-87-1	1125-05-87-2	1125-05-87-4			
	200 kgs (440 lbs)	Rubber on Cast	1125-05-03-1	1125-05-03-2	1125-05-03-4			
150mm x 38mm (6" x 1-1/2")	190 kgs (415 lbs)	Resilent Rubber on PA core	1125-06-10-1	1125-06-10-2	1125-06-10-4	Ball Bearing	187mm (7-3/8")	Swivel 113mm Swivel W/Brake 113mm
	180 kgs (396 lbs)	W Resolute	1125-06-64-1	1125-06-64-2	1125-06-64-4			



 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
150mm x 40mm (6" x 1-9/16")	350 kgs (770 lbs)	Nylon	1125-06-07-1	1125-06-07-2	1125-06-07-4	Ball Bearing	187mm (7-3/8")	Swivel 113mm Swivel W/Brake 113mm
	350 kgs (770 lbs)	WMRC	1125-06-45-1	1125-06-45-2	1125-06-45-4			
	250 kgs (550 lbs)	CPD	1125-06-49-1	1125-06-49-2	1125-06-49-4			
150mm x 42mm (6" x 1-11/16")	350 kgs (770 lbs)	PU on Cast	1125-06-33-1	1125-06-33-2	1125-06-33-4	Ball Bearing	187mm (7-3/8")	Swivel 113mm Swivel W/Brake 113mm
	400 kgs (880 lbs)	QPU	1125-06-80-1	1125-06-80-2	1125-06-80-4			
	400 kgs (880 lbs)	QPU on AL Core (Round)	1125-06-87-1	1125-06-87-2	1125-06-87-4			
	250 kgs (550 lbs)	NBR Rubber on Cast	1125-06-04-1	1125-06-04-2	1125-06-04-4			
150mm x 45mm (6" x 1-3/4")	220 kgs (485 lbs)	Rubber on Cast	1125-06-03-1	1125-06-03-2	1125-06-03-4	Ball Bearing	187mm (7-3/8")	Swivel 113mm Swivel W/Brake 113mm
200mm x 44mm (8" x 1-3/4")	300 kgs (660 lbs)	NBR Rubber on Cast	1125-08-04-1	1125-08-04-2	1125-08-04-4	Ball Bearing	240mm (9-7/16")	Swivel 140.5mm Swivel W/Brake 140.5mm
200mm x 48mm (8" x 1-7/8")	260 kgs (570 lbs)	Rubber on Cast	1125-08-03-1	1125-08-03-2	1125-08-03-4	Ball Bearing	240mm (9-7/16")	Swivel 140.5mm Swivel W/Brake 140.5mm
	300 kgs (660 lbs)	Resilient Rubber on PA core	1125-08-10-1	1125-08-10-2	1125-08-10-4			
200mm x 50mm (8" x 2")	400 kgs (880 lbs)	PU on Cast	1125-08-33-1	1125-08-33-2	1125-08-33-4	Ball Bearing	240mm (9-7/16")	Swivel 140.5mm Swivel W/Brake 140.5mm
	400 kgs (880 lbs)	QPU	1125-08-80-1	1125-08-80-2	1125-08-80-4			
	306 kgs (675 lbs)	W Resolute	1125-08-64-1	1125-08-64-2	1125-08-64-4			
	400 kgs (880 lbs)	Nylon	1125-08-07-1	1125-08-07-2	1125-08-07-4			
	400 kgs (880 lbs)	WMRC	1125-08-45-1	1125-08-45-2	1125-08-45-4			
	400 kgs (880 lbs)	QPU on AL Core (Round)	1125-08-87-1	1125-08-87-2	1125-08-87-4			
	400 kgs (880 lbs)	QPU on AL Core (Flat)	1125-08-87-1	1125-08-87-2	1125-08-87-4			
	300 kgs (660 lbs)	CPD	1125-08-49-1	1125-08-49-2	1125-08-49-4			